

Description

Dynac Semi-Traction is a semi-traction battery which provides energy for onboard energy consumers of motorhomes, caravans and boats or trucks and buses. These onboard energy consumers, such as lighting, refrigerators and onboard computers or tail lifts, demand massive cyclic performance of a battery. Dynac Semi-Traction is resistant to deep discharges up to 50% and is suitable for seasonal use. Ideal for leisure vehicles with light to medium power consumers. Available in a range of 12V batteries from 50Ah to 230Ah in series wet charged and sealed maintenance free (SMF).

Performance		
Nominal Voltage	12	
Capacity	90Ah (20hr, 1.75V/cell)	
Capacity	72Ah (5hr, 1.7V/cell)	
RC 25A	165	
CCA EN	590	

Dimensions / Casing / Weight				
Box Type	27			
Dimensions	Length: 303 mm Width: 172 mm Height: 200 mm Total Height: 223 mm			
Net Weight	21.3 Kg			
Acid Volume	6.8			
Material Casing / Lid	Polypropylene			

Technical Characteristics	
Technology	Flooded Calcium
Seperator	PE
Seperator	PE

Charging instructions	
Cycle use charge recommendation, Voltage	14.4 - 14.8
Cycle use charge recommendation, Max Amps	Min. 10% - max. 30%
Float charge recommendation, Voltage	13.38 - 13.8
Cycles at 50% DoD	350
Bulk charging = constant current	t = 20Hr current for recharge



Features

- Reliable power supply
- Deep discharges up to 50%
- Ideal for seasonal use
- Available as wet charged or sealed maintenance free (SMF)
- Recommended for leisure vehicles with light to medium power consumers

Layout	Terminal	Hold-down
+ -	5/16 "	100 max

Battery Classifications as per EN 50342-6					
Water Consumption	Charge Retention	Vibration Resistance	Endurance Level		
W4	C2	V2	E1		

(Note) All above information shall be changed without prior notice, Landport Batteries reserves the right to explain and update the latest information.







Description

Dynac Semi-Traction is a semi-traction battery which provides energy for onboard energy consumers of motorhomes, caravans and boats or trucks and buses. These onboard energy consumers, such as lighting, refrigerators and onboard computers or tail lifts, demand massive cyclic performance of a battery. Dynac Semi-Traction is resistant to deep discharges up to 50% and is suitable for seasonal use. Ideal for leisure vehicles with light to medium power consumers. Available in a range of 12V batteries from 50Ah to 230Ah in series wet charged and sealed maintenance free (SMF).

BATTERY CHARGE CONDITIONS (according DIN41773 and DIN 41774) Charging profiles: WaW0 and IUIa Charge factor: 1.10 – 1.20







Features

- Reliable power supply
- Deep discharges up to 50%
- Ideal for seasonal use
- Available as wet charged or sealed maintenance free (SMF)
- Recommended for leisure vehicles with light to medium power consumers

(Note) All above information shall be changed without prior notice, Landport Batteries reserves the right to explain and update the latest information.

