









Braille XC22.5-1125M6 Motorsport Lithium Battery

At only 4.0 KG, the XC22.5-1125M6 Motorsport Lithium Battery is a high-performance upgrade from a traditional lead acid battery. Offering significant weight reduction, more power output and lasting up to 5 times longer than lead acid batteries!

BENEFITS:

- Superior starting capabilities with high cranking amp output per kg
- Fast and efficient recharge, up to 5 times faster than lead acid batteries
- Can be used in "Total Loss" (no alternator) applications
- 3-5 times longer service life vs lead-acid batteries
- Engineered for high shock and vibration applications
- Up to 2/3 weight reduction for equivalent cranking performance

1125	4.0	22.5	288
10 SECONDS (A)	WEIGHT (KG)	CAPACITY (Ah)	CAPACITY (Wh)

PRODUCT INFORMATION

Physical Specs

Battery Chemistry	LFP
Length (mm)	254
Width (mm)	83
Height (mm)	156
Weight (kg)	4.0
Terminal Type	M6 stud
Polarity	Right +

Technical Specs

5 Second Pulse Cranking Amps	1698	Charging	0C to 50C
10 Second Pulse Discharge	1125	Temperature	00 10 300
Current (A)	1125	Discharge	-20C to +600
Voltage	12	Temperature Range	
Capacity (Ah)	22.5	Storage Temperature	-20C to +600
Capacity (Wh)	288		
Continuous Discharge Current (A)	450		

Charging

Recharge Voltage 14.4V - 14.6V Maintenance Charge Voltage 13.8V











